

Feature	VIA CN400	VIA CLE266
North Bridge		
Processor Support	VIA Eden™, VIA Antaur™ & VIA C3™ processors	VIA Eden™, VIA Antaur™ & VIA C3™ processors
Front Side Bus	200/133/100MHz	133/100/66MHz
Bus Architecture	Synchronous	Synchronous
Memory Support	FastStream64™ - Single Channel DDR400/333/266 SDRAM	Single Channel DDR266/200 or PC133/100 SDRAM
Max. Memory	4GB	2GB
External Graphics	AGP 8X/4X	AGP 8X/4X
Internal Graphics	S3 Graphics UniChrome™ Pro IGP	S3 Graphics UniChrome™ IGP
Video/Display	HDTV output MPEG4 hardware acceleration & MPEG2 decoder	MPEG2 hardware acceleration
South Bridge	VIA VT8237	VIA VT8235
North/South Bridge Link	Ultra V-Link (1066MB/sec)	V-link (266MB/sec)
Audio	VIA Vinyl™ 6-channel Audio (AC'97 integrated) VIA Vinyl™ Gold 8-channel Audio (PCI companion controller)	VIA Vinyl™ 6-channel Audio (AC'97 integrated)
Networking	VIA Velocity Gigabit Ethernet (PCI companion controller) VIA integrated 10/100 Fast Ethernet	VIA integrated 10/100 Fast Ethernet
Serial ATA	2 x SATA 150 devices SATALite™ interface for 2 additional SATA devices (4 total)	N/A
V-RAID	RAID 0, RAID 1, and RAID 0+1* & JBOD (SATA)	N/A
IDE	ATA133 (up to 4 devices)	ATA133 (up to 4 devices)
USB 2.0	8 ports	6 ports

PCI Devices/Slots	6 slots	6 slots
Modem	MC'97	MC'97
I/O Protocols	I/O APIC / LPC Super I/O	I/O APIC / LPC Super I/O
Power Management	ACPI/APM/PCI/PM	ACPI/APM/PCI/PM